Coloured Sheeting

Coloured roof sheeting is available in various profiles and colours. The most common profiles include: Corrugated, IBR, Widespan and Saflok. Material thickness includes: 0.5mm, 0.58mm and 0.8mm

The material thickness refers to Total Coated Thickness (TCT).

Please enquire, should you require the Base Metal Thickness (BMT).

What is the difference between Base Metal Thickness (BMT) and Total Coated Thickness (TCT)?

The Base Metal Thickness (BMT) measures the steel substrate prior to any matallic coating or paint being added to the substrade. The Total Coated Thickness (TCT) measures the steel substrate as well as the metallic coating and/ or paint film. In South Africa we generally refer to the thickness of material as the (TCT) of a product, however for design calculations or structural design you should use (BMT) since the actual strength of the material is from its base steel. The metallic coating layer is providing the corrosion resistance performance against natural weathering

Colour guidelines



^{*}The colour settings and quality of your monitor may influence the colour chart.

	Standard Colour Coatings	
Finishing	Chromadek	Colour Plus
Supplier	Arcelor Mittal	SAFAL
are	Fish Eagle White	Sea Spray
Please Note that the products we supply have different warranties that are supplied by the respective supplier.	White Lion	Chalk
	Dove Grey	Rain Cloud
	Dark Dolphin	Slate
	Charcoal	Thunderstorm
	Gemsbok Sand	Desert Sand
	Sandstone Beige	Savannah
	Buffalo Brown	Rustic Bark
	Kalahari Red	Sunset
	Azure Blue	Deep Ocean
	Kingfisher Blue	Island Sky
	Umhlanga Wave	No Match
	Traffic Green	Rain Forest
	Aloe Green	Aloe Green

Please Note:

The above are not identical matches

Care should be taken when ordering against existing colour orders